

# JOHNSON MANUFACTURING COMPANY

## Safety Data Sheet

To comply with 29CFR 1910.1200  
OSHA's Hazard Communication Standard

### Lloyd's #11 Stained Glass Flux, 04-90

#### 1. PRODUCT AND COMPANY INFORMATION

Johnson Manufacturing Company  
114 Lost Grove Road  
Princeton IA 52768

Emergency Telephone 1-(563)-289-5123  
CHEMTREC AFTER HOURS 1-(800)-424-9300  
Revised 1/1/2021 by JMC Product Safety

#### 2. HAZARD IDENTIFICATION

##### GHS Classification:

Eye Irrit 2  
Skin Corr. 1B  
STOT SE 3  
Flam. Liq. 2  
Acute Tox. 3 \*  
Acute Tox. 3 \*  
Acute Tox. 3 \*  
STOT SE 1



##### GHS Label Elements:

##### METHANOL & HYDROCHLORIC ACID DANGER

**H Codes:** H225, H301, H302, H311, H314, H331, H335, H319, H370

Toxic if swallowed

Toxic if inhaled

Causes severe skin burns and eye damage

Toxic in contact with skin

May cause drowsiness or dizziness

Causes damage to organs

Highly flammable liquid & vapor

Very toxic to aquatic life with long lasting effects

**P Codes:** P260, 280, 264, 301+330+331, 303+361+353, 363, 304+340, 310, 321, 305+351+338+310 405, 501, 261, 271, 312, 403+233, 337+313, 301+312, 210, 233, 240, 241, 242, 243, 403 + 235, 311, 302 + 352, 322, 361, 307 + 311

Avoid breathing dust/mist/vapors/fumes/spray. Do not get in eyes, on skin, or on clothing. Use in a well ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. In case of inadequate ventilation use respiratory protection. Do not eat, drink or smoke when using this product.

Keep away from heat, sparks or open flame – No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion proof electrical/ventilating/lighting and equipment. Use only non-sparking tools. Take precautionary measures against static discharge. In case of fire use foam or dry chemical for extinction. IF SWALLOWED: Rinse mouth. DO NOT induce vomiting. Immediately call a POISON CENTER/Doctor.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Wash with soap & water. Get medical advice/attention if you feel unwell. IF

INHALED: Remove victim to to fresh air and keep comfortable for breathing. Get medical advice/attention if you feel unwell. IF IN EYES: Rinse

cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call POISON

CENTER/Doctor. Wash thoroughly after use. Wash contaminated clothing before reuse. Store in a closed corrosive resistant container, with corrosive

resistant liner, in cool dry place. Avoid release to the environment. Dispose of contents/container in accordance with specified

local/regional/national/international regulations for disposal. Keep out of the reach of children. Read label and SDS prior to use.

#### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Component	CAS #	OSHA TWA	ACIGH TWA	Other limits	%
+ Methanol	67-56-1	200 ppm skin	200 ppm skin	NE	65 %
Polyethylene Glycol	25322-68-3	NE	NE	NE	
1-Aminoglutaric Acid Hydrochloride	138-15-8	NE	NE	NE	
+ Hydrogen chloride	7647-01-0	2ppm C	5ppm C	NE	5 %

C = Ceiling concentration

Only those ingredients listed in this section have been determined to be hazardous as defined in 29CFR 1910.1200.

An ingredient marked with an asterisk(\*) is also listed in 29CFR 1910.1200(D) #4 as a known or suspected cancer hazard.

+ Denotes a chemical regulated as toxic by the Environmental Protection Agency (EPA) as outlined in 40CFR Part 372 (Section 313)(SARA Title III).

## 4. FIRST AID MEASURES

---

**Signs and symptoms of exposure:** Inhalation-Nose & throat irritation, headache, dizziness, difficulty breathing, coughing. Ingestion-nausea, vomiting, cramps. Skin-redness, burning, rash, dryness. Eye-redness, burning, tearing, blurred vision.

**Emergency first aid procedures:**

Skin: Flush with water immediately - Seek medical attention if required.

Eyes: Flush with water for 15 minutes - Seek medical attention.

Ingestion: Drink large amounts of water, DO NOT induce vomiting- seek medical attention.

Never give anything by mouth to an unconscious person.

Inhalation: Remove to fresh air. Support respiration if required. Seek medical attention if required.

## 5. FIREFIGHTING MEASURES

---

**Extinguishing media:** Alcohol type foam, dry chemical, CO<sub>2</sub>.

**Special fire fighting procedures:** use self sustaining respiratory suit.

**Unusual Fire and Explosion Hazards:** Flammable liquid, water may spread flames. Excessive heat may cause sealed container to explode. May release hydrochloric acid, ammonia, chlorine, carbon dioxide, carbon monoxide fumes. Fumes may be heavier than air and may flashback.

## 6. ACCIDENTAL RELEASE MEASURES

---

**Methods and materials:** Flush into chemical sewer or soak up with a suitable absorbent. Wear adequate protection as described in section 8.

**Environmental Precautions:** Avoid release to the environment. Collect spillage.

## 7. HANDLING & STORAGE

---

Wash thoroughly after use. Wash contaminated clothing before reuse. Store in a closed corrosive resistant container, with corrosive resistant liner, in cool dry place. Keep out of the reach of children. Read label and SDS prior to use.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

---

**Occupational Exposure Limit Values:** See section 3.

Respiratory Protection (type): Acid mask required for fumes above TWA.

Ventilation: Local Exhaust preferred Special: NE

Mechanical: OK Other: NE

Protective Gloves: plastic or rubber Eye Protection: Goggles or face shield

Other Protective Clothing or Equipment: as required to avoid contact.

Work/Hygienic Practices: Wash after use. Follow good industrial hygienic practices.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

---

Boiling Point: 149 F

Specific Gravity: 0.87

Vapor Pressure (mm Hg): 96

Melting Point: NE

Vapor Density: NE

Evaporation Rate: 3.5 (butyl acetate=1)

Solubility in water: 100%

pH: NE

Flash Point: 52 F (TOC)

Flammable Limits: lel: 7.3 uel: 36.5

Appearance and odor: Clear to yellow liquid, alcohol odor.

## 10. STABILITY AND REACTIVITY

---

**Stability :** STABLE Conditions to avoid : none

**Incompatibility (materials to avoid):** strong bases & acids, oxidizers, sulfides, halogens.

**Hazardous Decomposition or Byproducts (incomplete combustion):** Hydrochloric acid, ammonia, chlorine, carbon dioxide, carbon monoxide, nitrogen oxides.

**Hazardous Polymerization:** WILL NOT OCCUR Conditions to avoid: none

## 11. TOXICOLOGICAL INFORMATION

---

**Routes of entry:** Inhalation? yes Skin? yes Ingestion? yes

**Health Hazards (acute and chronic):** Contact with fumes and material may cause skin, eye and respiratory tract irritation and burns. Ingestion may result in digestive tract irritation or burns. Ingestion of relatively small amounts may cause blindness and can cause death. May be mutagenic in lab animals. Material is flammable and will burn with a nearly invisible flame. Chronic exposures can result in permanent kidney and nervous system

depression. Effects are cumulative over many consecutive exposures via inhalation, ingestion and skin absorption. Studies show that potential health risks vary by individual. Always minimize exposure as a precaution.

**Carcinogenicity:** not determined NTP? no; IARC Monographs? no

## 12. ECOLOGICAL INFORMATION

---

**Toxicity:** NE

**Bio-accumulative Potential:** NE

**PBT & vPvB Assessment:** NE

**Persistence & Degradability:** NE

**Mobility in Soil:** NE

**Other Adverse Effects:** NE

## 13. DISPOSAL CONSIDERATIONS

---

**Waste Disposal Method:** dispose of in accordance with all local state and federal regulations

**Other Precautions:** Avoid skin & eye contact, inhalation & ingestion of fumes and material. Wash contaminated clothing before reuse. Keep away from children. Keep away from spark or flame.

## 14. TRANSPORT INFORMATION

---

**DOT Classification:** UN 1993 , Flammable Liquid NOS (Contains Methanol & Polyethylene Glycol), 3, PG II

**Marine Pollutant:** NE

## 15. REGULATORY INFORMATION

---

NFPA Classification (NFPA 325M, 8<sup>th</sup> edition)(Health, Flammability, Reactivity): 1-3-0

## 16. OTHER INFORMATION

---

The information and recommendations contained within this publication have been compiled from sources believed to be reliable and to represent the best information available to JOHNSON MANUFACTURING at the time of issue. No warranty, guarantee, or representation is made by JOHNSON MANUFACTURING nor does JOHNSON MANUFACTURING assume any responsibility in connection there within; nor can it be assumed that all acceptable safety measures or other safety measures may not be required under particular or exceptional conditions or circumstances.

---

NE = not established NA = not applicable

Form 303.78 Rev. D