JOHNSON MANUFACTURING COMPANY Safety Data Sheet

To comply with 29CFR 1910.1200 OSHA's Hazard Communication Standard

DayRod 820, 790-21C

1. PRODUCT AND COMPANY INFORMATION

Johnson Manufacturing Company 114 Lost Grove Road Princeton IA 52768 Emergency Telephone 1-(563)-289-5123 CHEMTREC AFTER HOURS 1-(800)-424-9300 Revised: 4/1/2023 by JMC Product Safety

2. HAZARD IDENTIFICATION

GHS Classification:

Tox. Organ3 Serious eye dam. 2 Skin Corr. 2 tox aqua 1

GHS Label Elements:

FLUOROALUMINATES & ZINC/ALUMINUM DANGER

H Codes: H301, H314, H319, H335, H400 Toxic if swallowed May be harmful if inhaled May cause respiratory irritation Causes severe skin burns and eye damage Very toxic to aquatic life

P Codes:

P264, 273, 261, 332 +313, 280, 337+313, 501, 302+352, 305+351+338, 403+233, 362, 304+340, 405,

Do not breath dust/mist/vapors/fumes/spray. Do not get in eyes, on skin, or on clothing. Use in a well ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. In case of inadequate ventilation use respiratory protection. Do not eat, drink or smoke when using this product. IF SWALLOWED: Rinse mouth. DO NOT induce vomiting. Immediately call a POISON CENTER/Doctor. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Wash with soap & water. If skin irritation occurs, get medical advise/attention. IF INHALED: Remove victim to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/Doctor. Do not eat, drink or smoke when using this product. lenses, if present and easy to do. Continue rinsing. Immediately call POISON CENTER/Doctor. Do not eat, drink or smoke when using this product. Wash thoroughly after use. Wash contaminated clothing before reuse. Store in a closed compatible container in cool dry place. Avoid release to the environment. Dispose of contents/container in accordance with specified local/regional/national/international regulations for disposal. Keep out of the reach of children. Do not handle until all safety precautions have been read and understood. Read label and SDS prior to use.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Component	CAS #	OSHA TWA	ACGIH TWA	Other Limits	Percent by Weight
cesium tetrafluoroaluminate	39211-00-2	2.5 mg/m3 fume	2.5 mg/m3 fume	NE	
+ Zinc (As Oxide)	7440-66-6	5 mg/m3	5 mg/m3	NE	75-85%
+ Aluminum	7429-90-5	15 mg/m3 dust	10 mg/m3 dust	5 mg/m3 fume	15-25%

Only those ingredients listed in this section have been determined to be hazardous as defined in 29CFR 1910.1200. An ingredient marked with an asterisk(*) is also listed in 29CFR 1910.1200(D) #4 as a known or suspected cancer hazard.

+ denotes a chemical regulated as toxic by the Environmental Protection Agency (EPA) as outlined in 40CFR Part 372 (section 313)

4. FIRST AID MEASURES

Signs and symptoms of exposure: Inhalation-Nose & throat irritation, headache, dizziness, difficulty breathing, coughing. Ingestion-nausea, vomiting, cramps. Skin-redness, burning, rash, dryness. Eye-redness, burning, tearing, blurred vision.

Medical conditions aggravated by exposure: Skin, kidney and respiratory conditions. Emergency first aid procedures:



Skin: Flush with water immediately - Seek medical attention if necessary

Eyes: Flush with water for 15 minutes - Seek medical attention

Ingestion: DO NOT induce vomiting, drink large amounts of water - seek medical attention. Never give anything by mouth to an unconscious person Inhalation: Remove to fresh air. Support respiration if required - Seek medical attention

5. FIREFIGHTING MEASURES

Extinguishing media: dry chemical. Special fire fighting procedures: use self sustaining respiratory suit. Unusual Fire and Explosion Hazards: May release metal & metal oxide fumes, hydrofluoric acid, fluorine, hydrocarbon fumes.

6. ACCIDENTAL RELEASE MEASURES

Methods and materials: Flush into chemical sewer or soak up with a suitable absorbent. Wear adequate protection as described in section 8. **Environmental Precautions:** Avoid release to the environment. Collect spillage.

7. HANDLING & STORAGE

Wash thoroughly after use. Wash contaminated clothing before reuse. Store in a closed corrosive resistant container, with corrosive resistant liner, in cool dry place. Keep out of the reach of children. Read label and SDS prior to use.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limit Values: See section 3. Respiratory Protection (type): HEPA/Organic/Acid mask required for fumes above TWA. Ventilation: Local Exhaust preferred Special: NE Mechanical: OK Other: NE Protective Gloves: plastic or rubber Eye Protection: Goggles or face shield Other Protective Clothing or Equipment: as required to avoid contact. Work/Hygienic Practices: Wash after use. Follow good industrial hygienic practices.

9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point: NESpecific Gravity: NEVapor Pressure (mm Hg): NEMelting Point: 698 – 806 FVapor Density: NEEvaporation Rate: <1 (butyl acetate=1)</td>Solubility in water: near NEpH: NEFlash Point: NE (TOC)Flammable Limits: lel: NE uel: NEAppearance and odor: Coated gray solid, odorless.

10. STABILITY AND REACTIVITY

Stability : STABLE Conditions to avoid : none

Incompatibility (materials to avoid): strong bases & acids, oxidizers, sulfides, halogens. Hazardous Decomposition or Byproducts (incomplete combustion): Metal & metal oxide fumes, hydrofluoric acid, fluorine, and hydrocarbons. Hazardous Polymerization: WILL NOT OCCUR Conditions to avoid: none

11. TOXICOLOGICAL INFORMATION

Routes of entry: Inhalation: yes Skin: yes Ingestion: yes

Health Hazards (acute and chronic): Contact with material and fumes may cause skin, eye and respiratory tract irritation. Gross inhalation may cause asthma. Ingestion may cause digestive tract irritation. Material is toxic by ingestion. Gross inhalation or ingestion may result in death. Material may be absorbed through skin. Repeated skin contact may result in absorption of harmful amounts. Chronic ingestion and inhalation exposures may result in embrittlement of bones, mottling of teeth, stiffening of ligaments and tendons (fluorosis), kidney and respiratory tract effects. May be mutagenic in lab animals. Studies show that potential health risks vary by individual. Minimize exposure as a precaution.

Carcinogenicity: not determined NPT? no IARC Monographs? no

12. ECOLOGICAL INFORMATION

Toxicity: NE Bio-accumulative Potential: NE Persistence & Degradability: NE Mobility in Soil: NE

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method: dispose of in accordance with all local state and federal regulations Other Precautions: Avoid skin & eye contact, inhalation & ingestion of fumes and material. Wash contaminated clothing before reuse. Keep away from children.

14. TRANSPORT INFORMATION

DOT Classification: Not regulated as dangerous goods IATA Classification: Not regulated as dangerous goods IMDG Classification: Not regulated as dangerous goods Marine Pollutant: NE

15. REGULATORY INFORMATION

NFPA Classification (NFPA 325M,8th edition)(Health, Flammability, Reactivity): 3-0-1

This product contains the following EPCRA section 313 chemicals subject to the reporting requirements of section 313 of the Emergency Response and Community Right-To-Know-Act of 1986 (40 CFR 372):

CAS Number	Chemical Name	Percent by Weight	
7440-66-6	Zinc (As Oxide)	75-85%	
7429-90-5	Aluminum	15-25%	

This information must be included in all SDSs that are copied and distributed for this material.

16. OTHER INFORMATION

The information and recommendations contained within this publication have been compiled from sources believed to be reliable and to represent the best information available to JOHNSON MANUFACTURING at the time of issue. No warranty, guarantee, or representation is made by JOHNSON MANUFACTURING assume any responsibility in connection there within; nor can it be assumed that all acceptable safety measures or other safety measures may not be required under particular or exceptional conditions or circumstances.

NE = not established NA = not applicable

Form 303.472 Rev. E